

SERIES IS-950



FEATURE SUMMARY

- Improves Safety & Productivity While Reducing Costs by Providing Protection From Inclement Weather, Dirt & Insects While Saving Energy
- High-Tear Abrasion Resistant 14 oz. Vinyl Bag Fabric With Double Lock Stitching
- Unique Retraction System Quickly Deflates & Returns Unit to Stored Position
- On/Off Switch With Pilot Light
- Galvanized Mounting Hardware
- Motor/Blower Mounted in Header
- Pressure Treated Superior Backing Lumber
- Condensation Drainage System
- Rigid Frame With Translucent Side & Top Covers
- Steel Protective Guards & Supports
- Galvanized Steel Mounting Hardware
- Bottom Corner Pads

DESCRIPTION

The IS-950 Series of inflatable dock shelters provide the ultimate protection for personnel and cargo while loading and off loading trailers. The inflated seal pushes tight against the sides and top of the trailer to help keep out inclement weather, dust and insects creating a more productive and safer environment while saving energy costs and increasing security.

OPERATION

Once the trailer is positioned against the bumpers for loading, the operator switches the control button to start the blower that in turn inflates the bag assemblies against the top and sides of the trailer creating a seal. The blower runs continuous as long as the loading or off loading is being carried out. When loading is complete, the operator turns off the switch and the shelter bags automatically retract away from the trailer.

CONSTRUCTION

The bags are constructed from flexible and UV resistant 16 oz. High-Tear vinyl fabric, double lock stitched and attached to the pressure treated lumber or optional steel framing. The 1/2 HP 115 volt or optional 230 volt motor/blower is integral mounted within the head frame. The on/off switch is mounted to the interior wall and equipped with a power on pilot light. A torsion spring retraction system is mounted within the head frame. Condensation drainage holes are provided in the bag assemblies. Heavy-duty steel guards are used to support and protect the side frames. Corner bottom pads seal the bottom side sections. All mounting hardware is galvanized steel.

WARRANTY

Nordock guarantees that the IS Model of inflatable dock shelters will perform as described and to the full satisfaction of the purchaser for one-year from date of receipt. Consult your Nordock representative for assistance in choosing the correct size and options for your application.

OPTIONS

16 oz. Hypalon Fabric
Automatic On/Off System
3 Phase Motor/Blower
Galvanized Steel Frame

ACCESSORIES

Loading Dock Lights
Dock Levelers
TRUCK-LOCK® Safety Vehicle Restraints



* Nordock Inc. reserves the right to make changes to specifications without notice or obligation.

NORDOCK INC.

Nordock products are covered by various U.S. and foreign patents & applications.

Website: www.nordockinc.com ~ Email: Sales@nordockinc.com ~ Toll Free: 866-885-4276